

INT/EXT READY MIXED LIGHT WEIGHT FILLER



GENERAL INFORMATION

Description

Light weight ready mixed filler

Intended use

Interior/exterior

- Filling holes and cracks of all sizes



PRODUCT ADVANTAGES

- + Excellent adhesion to substrates
- + Single-pass filling
- + No sanding required
- + Does not shrink or crack
- + Brilliant white

USE

DILUTION

Ready mixed

APPLICATION

Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

Equipment

Filling knife, blade.

Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMENDATIONS

Do not stir the paste once it has started to harden.

APPLICATION THICKNESS

Any thickness

AVERAGE CONSUMPTION

1 l/m²/mm thickness

SUBSTRATES

Concrete, cellular concrete, cement, brick, concrete block, gypsum board, old painted substrates.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

INT/EXT READY MIXED LIGHT WEIGHT FILLER



TECHNICAL DATA

COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives.
DENSITY	0.4 ± 0.05
pH	8.5 ± 1
COLOUR	White
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family IV - class 4b
NORM	NF EN 16566
V.O.C	< 5 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust.

In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING

4L, 750 ml, 250 ml bucket

STORAGE

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.