Ray's Shellac-Base Primer

Made for the Trade by the Trade

Product Description

Ray's Primer is produced in Cork by Donnelly Manufacturing who have being making shellac products for the last 70 years. It is an elite white shellac-based primer made from the highest grade of de-waxed shellac. Intended for interior use, as well as for spot-priming exterior substrate.

Key Properties

- High pigment and shellac content
- Excellent blocking & sealing properties: Odours/Stains/Graffiti/Knots
- Excellent adhesion to difficult substrate
- Dried film is non-toxic

Performance Characteristics

- Fast-drying Recoats in 45 minutes
- Excellent adhesion to glossy surfaces without scuff sanding
- Blocks stubborn and persistent stains.
 Including smoke stains and odours caused by fires
- Superior sealing properties
- Suitable for use on metal (aluminium, steel, stainless steel, copper).

Availability

1, 2.5 and 5L

Surface Preparation/Application

All surfaces must be cleaned down thoroughly to remove all dirt, grease, dust and loose materials. Ensure surface is sound and free from oil, grease, and mould.

Existing painted surface must be thoroughly sanded to provide a key for subsequent coat. Warning: Take special precautions when working on pre-1960's paint surfaces over wood and metal, as they may contain harmful lead. Wear suitable protective mask when sanding.

Before use

Eliminate all sources of ignition Stir well with wide flat stirrer.

Application method

Natural or synthetic brush, and/or roller. Spraying is not recommended for H&S and risk of fire reasons.

Drying Time

Ray's Primer will dry in 15-20 minutes in standard conditions. It can be sanded and recoated in 45 minutes. A dry primed surface will reach full adhesion and hardness within 72 hours. Lower temperatures and higher humidity will affect drying time. Not recommended to apply in conditions below 5°C

Coverage

12-14 m² per litre under normal conditions - will vary depending on method of application and substrate to be coated.

Clean up

Clean up any spill with methylated spirits. Remove excess from equipment, and then either soak in methylated spirits or household detergent. If brush hardens, leave to soak in methylated spirits or in Ray's Primer itself. Dispose of can and waste paint in accordance with local authority guidelines.

Storage

Inside, in a cool place.

Precautions

Caution: Flammable. Contains alcohol. Keep away from sparks, heat, and flame. Use only in well ventilated areas. Keep container closed when not in use. Keep out of reach of children. No smoking. If this product comes in contact with eyes wash immediately with water. To remove Ray's Primer from skin, wash with soap and water. Do not take internally. EU2010 Directive (CatA/i) 500g/l. Contains a max of 496g/l

Follow us on

Web: www.donnellymanufacturing.com Email:info@donnellymanufacturing.com

Phone: +353 (0)21) 4341315



