

DANISH OIL 1

Page: 1

Compilation date: 08/02/2017

**Revision date:** 19/10/2020

Revision No: 4

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: DANISH OIL 1

Product code: DANO

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX

United Kingdom **Tel:** +44 (0)208 450 4666

Fax: +44 (0)208 452 2008
Email: rustins@rustins.co.uk

## 1.4. Emergency telephone number

**Emergency tel:** .+44(0)2084504666 (Office hours only)

## **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066; -: EUH208

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Contains cobalt 6, methyl ethyl

ketoxime, 2-octyl-2h-isothiazol-3-one. May produce an allergic reaction. Flammable

liquid and vapour. May cause drowsiness or dizziness.

## 2.2. Label elements

## Label elements:

UFI: 79H4-NSFT-651M-A80J

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains cobalt 6, methyl ethyl ketoxime, 2-octyl-2h-isothiazol-3-one. May

produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

DANISH OIL 1

Page: 2





Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves and eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P370+P378: In case of fire: Use media other than water to extinguish.

## 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

# 3.2. Mixtures

## Hazardous ingredients:

## LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

| EINECS      | CAS           | PBT / WEL     | CLP Classification  | Percent                               |
|-------------|---------------|---------------|---|---------------------------------------|
| 265-150-3   | 64742-48-9    | -             | Asp. Tox. 1: H304; Flam. Liq. 3: H226   | 44.170%                               |
| NAPTHA (PET | ROLEUM) HYDRC | TREATED HEAVY |   |                                       |
| 265-150-3   | 64742-48-9    | -             | -   | 20.734%                               |
| COBALT 6    |               |               |   |                                       |
| -           | 13586-82-8    | -             | Eye Irrit. 2: H319; Skin Sens. 1: H317;<br>Repr. 2: H361f; Aquatic Chronic 3:<br>H412 | 0.590%                                |
| 2-ETHYLHEXA | ANOIC ACID    |               |   | · · · · · · · · · · · · · · · · · · · |
| 205-743-6   | 149-57-5      | -             | Repr. 2: H361d  | 0.215%                                |
| METHYL ETH  | YL KETOXIME   |               |   |                                       |
| -           | 96-29-7       | -             | Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317               | 0.138%                                |

**DANISH OIL 1** 

Page: 3

#### **METHANOL**

| 200-659-6    | 67-56-1        | - | Flam. Liq. 2: H225; Acute Tox. 3: H331;<br>Acute Tox. 3: H311; Acute Tox. 3: H301;<br>STOT SE 1: H370 | 0.130% |
|--------------|----------------|---|---|--------|
| 2-OCTYL-2H-I | SOTHIAZOL-3-ON | E |   |        |
| 247-761-7    | 26530-20-1     | - | Acute Tox. 3: H331; Acute Tox. 3: H311;   | 0.019% |
|              |                |   | Acute Tox. 4: H302; Skin Corr. 1B:  |        |
|              |                |   | H314; Skin Sens. 1: H317; Aquatic   |        |
|              |                |   | Chronic 1: H410; Aquatic Acute 1:   |        |
|              |                |   | H400  |        |

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## **Section 5: Fire-fighting measures**

## 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

**DANISH OIL 1** 

Page: 4

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

## 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

## 8.1. Control parameters

Hazardous ingredients:

**DANISH OIL 1** 

Page: 5

#### **METHANOL**

#### Workplace exposure limits:

#### Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK    | 266 mg/m3  | 333 mg/m3    | -          | -            |

#### 2-OCTYL-2H-ISOTHIAZOL-3-ONE

| LIIZ | 0.05 mg/m2 | 0.05 mg/m2 |   |   |
|------|------------|------------|---|---|
| UK   | 0.05 mg/m3 | 0.05 mg/m3 | - | - |

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community

environmental legislation.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Paraffinic.

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Also soluble in: Benzene. Most organic solvents.

Viscosity: Oily

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 38 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.84 @ 20C pH: No data available.

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

**DANISH OIL 1** 

Page: 6

## Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

# Hazardous ingredients:

## 2-ETHYLHEXANOIC ACID

| ORL | RAT | LD50 | 3    | gm/kg |
|-----|-----|------|------|-------|
| SKN | RBT | LD50 | 1260 | μl/kg |

## **METHANOL**

| IVN | RAT | LD50 | 2131 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 7300 | mg/kg |
| ORL | RAT | LD50 | 5628 | mg/kg |

#### 2-OCTYL-2H-ISOTHIAZOL-3-ONE

| ORL | RAT | LD50 | 550 | mg/kg |
|-----|-----|------|-----|-------|
| SKN | RBT | LD50 | 690 | mg/kg |

#### Relevant hazards for product:

| Hazard               | Route | Basis                 |
|----------------------|-------|-----------------------|
| STOT-single exposure | -     | Hazardous: calculated |

**DANISH OIL 1** 

Page: 7

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

#### 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### **Section 13: Disposal considerations**

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1263

## 14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid

lacquer base

**DANISH OIL 1** 

Page: 8

## 14.3. Transport hazard class(es)

Transport class: |||

## 14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: Yes

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

## **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

## Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains cobalt 6, methyl ethyl ketoxime, 2-octyl-2h-isothiazol-3-one. May

produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

DANISH OIL 1

Page: 9

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H361d: Suspected of damaging the unborn child.

H361f: Suspected of damaging fertility.

H370: Causes damage to organs.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.